

200 - 300 GHK

HYDROMANN

Salt-og grit spreader 200 - 300 G/H/K

One of the most sold spreaders in Denmark for compact tractors. This spreader is powered either by hydraulic, PTO or drive-wheel. With all the diverse accessories, this machine satisfies client demands for a flexible multi-task unit. The simple construction with strong durable parts ensures low cost maintenance. This machine works under all road and weather conditions, and can manage the harshest of salt-spreading conditions. For the correct dosage with the drive-wheel model, a gear wheel is chosen which is compatible with the spread material. There is also protection on the actuator, so that it cannot be damaged or overload the drive wheel. For minimum salt spreading, special cams can be mounted to achieve dosage of 10 gr. m²



Salt and grit spreader:

- > Roller with replaceable cams
- > Agitator
- > Grating
- > Adjustable spring base
- > Emptying function
- > 3-point hitch cat. 0-1



Hydromann a/s, Nylandsvej 36, DK-6940 Lem St.
Tlf.: +45 97 34 12 33 - Fax: +45 97 34 19 09.
Sales@hydromann.dk - www.hydromann.dk

Technical details (200 - 300 GHK)


Total width	116 - 142 cm
Spread width	100 - 126 cm
Capacity	190 - 240 litre
Spread distance: Salt at 20 gr./m²	11 km
Spread distance: Sand at 200 gr./m²	2 km
Weight	110 - 145 kg
Oil requirement	18 litre / 100 bar
Surface treatment	Zinc + Primer + 2 component top coat



Grating

Accessories:

- Hopper extension
- Various cams
- Flow regulation
- Drive-dependent control
- Tarpaulin
- Lighting
- Lifting unit



Adjustment of spring base



3-point hitch cat. 0-1

HYDROMANN

Forhandler:

Hydromann a/s
Nylandsvej 36
DK-6940 Lem St.
Tlf.: +45 97 34 12 33
Fax: +45 97 34 19 09.
www.hydromann.dk