

200 V/F/P • 200 • 300 • 400 • 700 • 800 • 900

# Fendt ISU



**FENDT**



# Technical Specifications

	Fendt 200 Vario V F P				
	207 V/F	208 V/F	209 V/F/P	210 V/F/P	211 V/F/P
<b>Engine</b>					
Rated power (kW/hp) ECER24	44/60	52/70	59/80	66/90	74/100
Max. power (kW/hp) ECER24	51/70	59/80	67/90	73/100	81/110
Rated power (kW/hp) EC 97/68	52/71	60/82	67/91	73/99	74/101
Max. power (kW/hp) EC 97/68	55/75	63/85	70/95	77/105	85/115
No. of cylinders/cooling	3/Wasser	3/Wasser	3/Wasser	3/Wasser	3/Wasser
Bore/stroke (mm)	108/120	108/120	108/120	108/120	108/120
Cubic capacity (cm <sup>3</sup> )	3300	3300	3300	3300	3300
Rated engine speed (rpm)	2100	2100	2100	2100	2100
Opt. fuel consumption (g/kWh)	212	212	210	210	210
Max. torque (Nm/rpm) 1600 rpm	295	337	373	408	458
Torque rise (%)	35	32	30	30	44
Fuel tank capacity (l)	76	76	76	76	76
<b>Transmission and PTO</b>					
Type	stepless Vario transmission				
Speed range (forward / reverse)	4WD: 0.02 to 40 km/h / 0.02 to 25 km/h Rear wheel drive: 0.02 to 30 km/h / 0.02 to 25 km/h				
Maximum speed RWD/4WD (km/h) <sup>2)</sup>	35/40	35/40	40	40	40
Powershift rear PTO standard optional	540 / 540E / 1000 540 / 540E / ground PTO <sup>1)</sup> 540 or 1000 <sup>1)</sup>				
Powershiftable front PTO (optional) <sup>1)</sup>					
<b>Hydraulics</b>					
Type	EPC with shock load stabilising or EHL position control <sup>1)</sup>				
Control	free floating, position, draft and stepless mix control				
Hydraulic pump capacity (l/min)	Tandem pump (35+41), load-sensing system with displacement pump (35+71) <sup>1)</sup>				
Working pressure (bar)	200	200	200	200	200
Auxiliary control valves, max. centre/rear	6/4	6/4	6/4	6/4	6/4
Max. available oil volume (l)	25	25	25	25	25
Flow volume control valves	all valves: 0-40 litres, 3rd valve with 0-65 litres <sup>1)</sup>				
<b>Brakes</b>					
Rear brakes	wet ring piston brake				
Four-wheel braking system for 4WD/RWD	automatic 4WD engagement / hydraulic drum brake				
<b>Electrical equipment</b>					
Battery (Ah)	50				
Three-phase alternator	14 V / 120 A				

	Standard tyres				
	Tyres RWD		Track min. track		minimum width
	front	rear	front	rear	rear
207 / 208 V	7.50-16 7.50-16	280/85R24 320/85R24	940 940	777 831	1070 1151
207 - 211 VA	4WD front rear				
	7.5L15 10.0/75-15.3 280/70R16	280/85R24 320/85R24 360/70R24	794 844 852	777 831 857	1070 1151 1217
207 - 208 F	RWD 7.50R16 12.4R28 13.6R28		940	1000 1000	1322 1372
207 - 211 FA	280/70R18 280/80R18	12.4R28 13.6R28	1064 1064	1000 1000	1322 1372
209 - 211 PA	280/80R18 280/70R20	380/85R28 420/70R28	1212 1212	1288 1288	1668 1703

<sup>1)</sup> Optional

<sup>2)</sup> Speed depends on tyres

	207		208		209			210			211		
	V/VA	F/FA	V/VA	F/FA	VA	FA	PA	VA	FA	PA	VA	FA	PA
<b>Weights and dimensions</b>													
Unladen weight with cab (kg)	2780	2860	2780	2860	2780	2860	3080	2780	2860	3080	2780	2860	3080
Unladen weight with safety bar (kg)	2580	---	2580	---	2580	---	2860	2580	---	2860	2580	---	2860
Max. perm. overall weight RWD/4WD (kg)	4000/4500	4000/4500	4000/4500	4000/4500	4500	4500	5300	4500	4500	5300	4500	4500	5300
Max. hitch load (kg)	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
Overall length (mm)	3578	3683	3578	3683	3578	3683	3701	3578	3683	3701	3578	3683	3701
Overall width narrow/wide (mm)	1070/1161	1340	1151/1269	1372	1151/1269	1372	1679	1269/1269	1372	1679	1305/1305	1372	1717
Wheelbase (mm)	2160	2160	2160	2160	2160	2160	2160	2160	2160	2160	2160	2160	2160
Overall height comfort cab (mm)	2360	2443	2390	2462	2390	2462	2486	2390	2462	2486	2390	2462	2488
Overall height low roof version (mm)	2210	2293	2240	2312	2240	2312	2336	2240	2312	2336	2240	2312	2338
Overall height safety bar high (mm)	2383	---	2413	---	2413	---	2509	2413	---	2509	2413	---	2511
<b>Hydraulics</b>													
Max. lift capacity, rear linkage (daN)	2775	2417	2775	2417	2775	2417	3134	2775	2417	3134	2775	2417	3134
Max. lift capacity, front linkage (daN) <sup>1)</sup>	2390	2390	2380	2390	2380	2390	2540	2390	2390	2540	2390	2390	2540

	Fendt 200 Vario					Fendt 300 Vario			
	207	208	209	210	211	309	310	311	312
<b>Engine</b>									
Rated power (kW/hp) (ECE R24)	44 / 60	52 / 70	59 / 80	66 / 90	74 / 100	59 / 80	66 / 90	74 / 100	81 / 110
Max. power (kW/hp) (ECE R24)	51 / 70	59 / 80	67 / 90	73 / 100	81 / 110	70 / 95	77 / 105	84 / 115	92 / 125
Rated power (kW/hp) (EC 97/68) <sup>2)</sup>	52 / 71	60 / 82	67 / 91	73 / 99	74 / 101	69 / 94	73 / 99,5	84 / 114	91 / 124
Max. power (kW/hp) (EC 97/68)	55 / 75	63 / 85	70 / 95	77 / 105	85 / 115	73 / 99	80 / 109	88 / 119	95 / 129
No. of cylinders / cooling / aspiration	3 cylinders / water / turbocharger, intercooler					4-cylinders, 4-valve technology / water / turbocharger, intercooler			
Injection / engine control / exhaust recirculation	common rail / EDC / external EGR					common rail / EDC / external EGR			
Bore / stroke (mm) / cubic capacity (cm <sup>3</sup> )	108/120/3300					101/126/4038			
Rated engine speed (rpm)	2100	2100	2100	2100	2100	2100	2100	2100	2100
Engine speed at max. power (rpm)	1900	1900	1900	1900	1900	1900	1900	1900	1900
Max. torque (Nm/rpm)	295 / 1600	337 / 1600	373 / 1600	408 / 1600	458 / 1600	407 / 1450	445 / 1450	485 / 1450	515 / 1450
Torque rise (%)	34	32	30	30	42	40	44	35	32
Optim. fuel consumption (g/kWh)	207	207	207	207	207	207	206	206	206
Fuel tank (l)	125	125	125	125	125	210	210	210	210
Oil change interval (op. hrs.) <sup>6)</sup>	500	500	500	500	500	500	500	500	500
<b>Transmission and PTO</b>									
Type	stepless Vario transmission					continuously variable Vario transmission			
Speed range I: (forward / reverse)	0.03 to 40 km/h / 0.03 to 25 km/h					0.03 to 40 km/h / 0.02 to 25 km/h			
Speed range II: (forward / reverse)									
Maximum speed (km/h)	40	40	40	40	40	40	40	40	40
Rear PTO (rpm) standard (optional)	540 / 540E / 1000 ground PTO <sup>1)</sup>					540 / 540E / 1000 (540 / ground PTO (7.9 rev/driven metre) <sup>1)</sup> )			
Front PTO <sup>1)</sup>	540 or 1000					540 or 1000			
<b>Hydraulics</b>									
Type	Electrohydr. power lift control (EPC) with shock load stabilising					constant flow system			
Hydraulic pump capacity (l/min)	48 (41+35) <sup>1)</sup>	48 (41+35) <sup>1)</sup>	48 (41+35) <sup>1)</sup>	48 (41+35) <sup>1)</sup>	48 (41+35) <sup>1)</sup>	78 (48+30)	78 (48+30)	78 (48+30)	78 (48+30)
Working pressure (bar)	200	200	200	200	200	200	200	200	200
Rear linkage control	EPC, lower link control, shock load stabilising					EPC, lower link control, shock load stabilising			
Max. auxiliary valves, (standard) incl. front controls	4 da <sup>4)</sup> (2 da <sup>4)</sup> ) valves / crossgate lever					4 da <sup>4)</sup> (2 da <sup>4)</sup> ) valves / crossgate lever			
Max. lift capacity, rear lift on the drawbar (kN/kp)	4204	4204	4204	4204	4204	5280	5280	5280	5280
Max. lift capacity, front lift (daN)	2490	2490	2490	2490	2490	2940	2940	2940	2940
Max. available hydraulic oil (l)	28	28	28	28	28	42	42	42	42
<b>Brakes</b>									
Rear brakes	wet ring piston brake					wet, integrated ring piston brake			
Brakes front Four-wheel drive version:	automatic 4WD engagement					4WD engagement			
Rear wheel drive version:						drum brake <sup>9)</sup> drum brake <sup>9)</sup>			
<b>Weights and dimensions</b>									
Unladen weight	3750	3790	3870	3870	3930	4130 (3800 <sup>9)</sup> )	4130 (3800 <sup>9)</sup> )	4190	4350
Perm. overall weight (kg)	7000	7000	7000	7000	7000	8000 (6000 <sup>9)</sup> )	8000 (6000 <sup>9)</sup> )	8000	8000
Max. payload (kg)	3250	3210	3130	3130	3070	3870 (2200 <sup>9)</sup> )	3870 (2200 <sup>9)</sup> )	3810	3650
Max. hitch load (kg)	2000	2000	2000	2000	2000	2000	2000	2000	2000
Overall length (mm)	4068	4068	4068	4068	4068	4150	4150	4150	4150
Overall width (mm)	1970	2170	2170	2170	2186	2165	2275	2275	2385
Overall height (mm)	2477	2482	2530	2530	2525	2740	2745	2745	2790
Ground clearance <sup>3)</sup> (mm)	475	475	475	475	475	436	436	436	476
Wheelbase (mm)	2294	2294	2294	2294	2294	2350	2350	2350	2350
Front track <sup>3)</sup> (mm)	1500	1500	1690	1690	1690	1685 (1580 <sup>9)</sup> )	1685 (1580 <sup>9)</sup> )	1685	1820
Rear track <sup>3)</sup> (mm)	1510	1655	1660	1660	1660	1660	1660	1660	1800
Min. turning circle (m)	3,98	3,98	3,98	3,98	3,98	4,4 (4,1 <sup>9)</sup> )	4,4 (4,1 <sup>9)</sup> )	4,5	4,5
<b>Electrical equipment</b>									
Starter (kW)	3.0					3.0			
Battery	12V / 90Ah					12V / 90Ah			
Alternator	14V / 120 A					14V / 143 A			
<b>Cab</b>									
Type	integral safety cell					integral safety cell			
Climate control	hinged tinted front, side and rear windows, roof hatch, ventilation system with blower in roof, hot water heating with 3-speed blower, air-conditioning <sup>1)</sup>					hinged, tinted front, side and rear windows, roof hatch, ventilation system with blower in roof, hot water heating with 3-speed blower, air-conditioning <sup>1)</sup>			
<b>Tyres</b>									
Front tyres (standard)	320/70R24	320/70R24	380/70R24	380/70R24	440/65R24	380/70R24	440/65R24	440/65R24	480/65R24
Rear tyres (standard)	420/85R30	480/70R30	480/70R34	480/70R34	540/65R34	480/70R34	540/65R34	540/65R34	540/65R38

<sup>1)</sup> = optional <sup>2)</sup> = Power specifications for registration, <sup>3)</sup> = with standard tyres, <sup>4)</sup> = can also be used as single-acting, <sup>5)</sup> = depending on country regulations, <sup>6)</sup> = SHPD oil, <sup>7)</sup> = is halved when using RME, <sup>8)</sup> = without steering brake <sup>9)</sup> = rear-wheel drive version, <sup>10)</sup> = for perm. overall weight of 7500 kg, <sup>11)</sup> = only Profi version with dual-circuit braking system, <sup>12)</sup> = optional single-circuit braking system, only 50 km/h, <sup>13)</sup> = depends on the braking system and perm. top speed, <sup>14)</sup> = Power version (50 km/h) <sup>15)</sup> = Profi version (60 km/h)

# Technical Specifications

	Fendt 400 Vario					Fendt 700 Vario			
	411	412	413	414	415	712	714	716	718
<b>Engine</b>									
Rated power (kW/hp) (ECE R24)	74 / 100	81 / 110	88 / 120	96 / 130	103 / 140	85 / 115	96 / 130	110 / 150	121 / 165
Max. power (kW/hp) (ECE R24)	85 / 115	92 / 125	99 / 135	107 / 145	114 / 155	96 / 130	107 / 145	121 / 165	132 / 180
Rated power (kW/hp) (EC 97/68) <sup>2)</sup>	84 / 114	91 / 124	98 / 134	106 / 144	113 / 154	97 / 132	108 / 147	123 / 167	129 / 175
Max. power (kW/hp) (EC 97/68)	88 / 120	96 / 130	103 / 140	110 / 150	118 / 160	100 / 136	111 / 151	126 / 172	137 / 186
No. of cylinders / cooling / aspiration	4-cylinders, 4-valve technology / water / turbocharger, intercooler					6-cylinders, 4-valve technology / water / turbocharger,			
Injection / engine control / exhaust recirculation	common rail / EDC / external EGR					intercooler common rail / EDC / AGReX			
Bore / stroke (mm) / cubic capacity (cm <sup>3</sup> )	101/126/4038					101/126/6056			
Rated engine speed (rpm)	2100	2100	2100	2100	2100	2100	2100	2100	2100
Engine speed at max. power (rpm)	1900	1900	1900	1900	1900	1900	1900	1900	1900
Max. torque (Nm/rpm)	505 / 1400	550 / 1400	589 / 1400	613 / 1400	657 / 1400	571 / 1450	640 / 1450	724 / 1450	780 / 1450
Torque rise (%)	42	42	41	35	35	38	38	36	35
Optim. fuel consumption (g/kWh)	205	205	204	203	204	198	198	195	195
Fuel tank (l)	245	245	245	245	245	340	340	340	340
AdBlue	-	-	-	-	-	-	-	-	-
Oil change interval (op. hrs.) <sup>6)</sup>	500	500	500	500	500	500	500	500	500
<b>Transmission and PTO</b>									
Type	continuously variable Vario transmission					continuously variable Vario transmission			
Speed range I: (forward / reverse)	0.02 to 24 km/h / 0.02 to 17 km/h					0.02 to 28 km/h / 0.02 to 17 km/h			
Speed range II: (forward / reverse)	0.02 - 50 <sup>5)</sup> km/h / 0.02 - 40 km/h					0.02 - 50 <sup>5)</sup> km/h / 0.02 - 40 km/h			
Maximum speed (km/h)	50 <sup>5)</sup>	50 <sup>5)</sup>	50 <sup>5)</sup>	50 <sup>5)</sup>	50 <sup>5)</sup>	50 <sup>5)</sup>	50 <sup>5)</sup>	50 <sup>5)</sup>	50 <sup>5)</sup>
Rear PTO (rpm) standard (optional)	540 / 540E / 1000					540 / 540E / 1000			
Front PTO <sup>1)</sup>	540 or 1000					540 or 1000			
<b>Hydraulics</b>									
Type	load sensing					load sensing			
Hydraulic pump capacity (l/min)	75 (110 <sup>1)</sup> )	75 (110 <sup>1)</sup> )	75 (110 <sup>1)</sup> )	75 (110 <sup>1)</sup> )	75 (110 <sup>1)</sup> )	110 (154 <sup>1)</sup> )	110 (154 <sup>1)</sup> )	110 (154 <sup>1)</sup> )	110 (154 <sup>1)</sup> )
Working pressure (bar)	200	200	200	200	200	200	200	200	200
Rear linkage control	EPC, lower link control, shock load stabilising					EPC, lower link control, shock load stabilising			
Max. auxiliary valves, (standard) incl. front controls	4 da <sup>4)</sup> (2 da <sup>4)</sup> ) electr. valves / crossgate lever					5 da <sup>4)</sup> (3 da <sup>4)</sup> ) electr. valves / crossgate lever			
Max. lift capacity, rear lift on the drawbar (kN/kp)									
Max. lift capacity, front lift (daN)	6520	6520	6520	6520	6520	8340	8340	8340	9080
Max. available hydraulic oil (l)	3100	3100	3100	3100	3100	4440	4440	4440	4440
	38	38	38	38	38	45	45	45	45
<b>Brakes</b>									
Rear brakes	wet, integrated multi-disc brake					wet, integrated multi-disc brake			
Brakes front	Four-wheel drive version: 4WD engagement					wet brakes on cardan shaft			
	Rear wheel drive version:								
<b>Weights and dimensions</b>									
Unladen weight	5400	5400	5420	5450	5450	6605	6605	6605	6985
Perm. overall weight (kg)	9000 (7500 <sup>1)</sup> )	9000 (7500 <sup>1)</sup> )	9000 (7500 <sup>1)</sup> )	9500 (7500 <sup>1)</sup> )	9500 (7500 <sup>1)</sup> )	11500 (7500 <sup>1)</sup> )	11500 (7500 <sup>1)</sup> )	11500 (7500 <sup>1)</sup> )	12500
Max. payload (kg)	3600 (2100 <sup>10)</sup> )	3600 (2100 <sup>10)</sup> )	3580 (2080 <sup>10)</sup> )	4050 (2050 <sup>10)</sup> )	4050 (2050 <sup>10)</sup> )	4895 (895 <sup>10)</sup> )	4895 (895 <sup>10)</sup> )	4895 (895 <sup>10)</sup> )	5515
Max. hitch load (kg)	2000	2000	2000	2000	2000	2000	2000	2000	2000
Overall length (mm)	4252	4252	4242	4281	4281	4669	4669	4669	4753
Overall width (mm)	2340	2340	2380	2440	2490	2520	2520	2570	2570
Overall height (mm)	2900	2900	2923	2923	2953	2960	2999	2999	2999
Ground clearance <sup>3)</sup> (mm)	462	462	482	482	512	552	552	552	552
Wheelbase (mm)	2417	2417	2417	2417	2417	2700	2700	2700	2720
Front track <sup>3)</sup> (mm)	1820	1820	1820	1880	1880	1940	1940	1940	1940
Rear track <sup>3)</sup> (mm)	1800	1800	1800	1860	1860	1920	1920	1920	1920
Min. turning circle (m)	4,95	4,95	4,95	4,75	4,75	5,5	5,5	5,5	5,5
<b>Electrical equipment</b>									
Starter (kW)						3.0			
Battery						12V / 90Ah			
Alternator						14V / 200 A			
<b>Cab</b>									
Type and climate control	integral, tiltable safety cell hinged, tinted front, side and rear windows, roof hatch, ventilation system with blower in roof, hot water heating with 3-speed blower, air-conditioning <sup>1)</sup>					integral, tiltable safety cell hinged, tinted front, side and rear windows, roof hatch, ventilation system with inf. adj. blower in roof, hot water heating with three-speed blower, air-conditioning			
<b>Tyres</b>									
Front tyres (standard)	480/65R24	480/65R24	540/65R24	540/65R24	540/65R26	480/65R28	480/70R28	540/65R28	540/65R28
Rear tyres (standard)	540/65R38	540/65R38	600/65R38	600/65R38	650/65R38	600/65R38	580/70R38	650/65R38	650/65R38

**Additional implement line:** A comprehensive line of additional implements is available for year round operations. Additional implements are selected by Fendt and optimally adapted to the Vario tractors with the implement manufacturers.

Fendt700 Vario			Fendt 800 Vario				Fendt 900 Vario					
720	722	724	822	824	826	828	924	927	930	933	936	939
136 / 185 147 / 200 148 / 201 153 / 208	151 / 205 162 / 220 163 / 222 168 / 229	162 / 220 176 / 240 174 / 237 181 / 246	147 / 200 162 / 220 159 / 216 166 / 226	162 / 220 176 / 240 174 / 237 182 / 248	176 / 240 191 / 260 188 / 256 195 / 265	191 / 260 206 / 280 203 / 276 211 / 287	154 / 210 176 / 240 172 / 234 180 / 245	176 / 240 199 / 270 194 / 264 202 / 275	199 / 270 220 / 300 217 / 295 224 / 305	220 / 300 242 / 330 238 / 324 245 / 333	243 / 330 265 / 360 261 / 355 269 / 366	265 / 360 287 / 390 276 / 376 291 / 396
6-cylinders / water common rail / EDC / - 101/126/6056			6-cylinders / water common rail / EDC / - 101/126/6056				6-cylinders / water Common-Rail / EDC / - 110/136/7755					
2100 1800 897/1450 39 192 400 38 500	2100 1800 988/1450 39 192 400 38 500	2100 1800 1058/1450 38 192 400 38 500	2100 1900 955 / 1450 37 192 505 42 500	2100 1900 1040 / 1450 36 192 505 42 500	2100 1900 1120 / 1450 35 192 505 42 500	2100 1900 1210 / 1450 35 192 505 42 500	2200 1900 1049 / 1450 36 197 600 60 500	2200 1900 1116 / 1450 36 197 600 60 500	2200 1900 1234 / 1450 34 198 600 60 500	2200 1900 1326 / 1450 31 198 600 60 500	2200 1900 1498 / 1450 34 198 600 60 500	2200 1900 1547 / 1450 31 195 600 60 500
continuously variable Vario transmission 0.02 to 28 km/h / 0.02 to 17 km/h 0.02 - 50 <sup>5)</sup> km/h / 0.02 - 40 km/h 50 <sup>5)</sup>			continuously variable Vario transmission 0.02 to 34 km/h / 0.02 to 20 km/h 0.02 to 60 km/h <sup>5)</sup> / 0.02 to 33 km/h 60 <sup>5)</sup> 11)				continuously variable Vario transmission 0.02 to 34 km/h / 0.02 to 20 km/h 0.02 to 60 km/h <sup>5)</sup> / 0.02 to 33 km/h 60 <sup>5)</sup> 11)					
540 / 540E / 1000 540 or 1000			540E / 1000 (1000 / 1000E) 1000				540E / 1000 (1000 / 1000E) 1000					
load sensing 109 (152)    109 (152)    109 (152)			load sensing 152 (193 <sup>1)</sup> )    152 (193 <sup>1)</sup> )    152 (193 <sup>1)</sup> )    152 (193 <sup>1)</sup> )				load sensing 160 (216 <sup>1)</sup> )    160 (216 <sup>1)</sup> )    160 (216 <sup>1)</sup> )    160 (216 <sup>1)</sup> )    160 (216 <sup>1)</sup> )    160 (216 <sup>1)</sup> )					
EPC, lower link control, shock load stabilising / 5 da <sup>4)</sup> (3 da <sup>4)</sup> ) electr. valves / crossgate lever			EPC, lower link control, shock load stabilising 4 da <sup>4)</sup> (3 da <sup>4)</sup> ) - 8 da <sup>4)</sup> (4 da <sup>4)</sup> ) el. valves				EPC, lower link control, shock load stabilising 4 da <sup>4)</sup> (3 da <sup>4)</sup> ) - 8 da <sup>4)</sup> (4 da <sup>4)</sup> ) el. valves / crossgate lever					
9580 4418 3180	9580 4418 3180	9580 4418 3180	11110 5030 80	11110 5030 80	11110 5030 80	11110 5030 80	1180 5550 87	1180 5550 87	1180 5550 87	1180 5550 87	1180 5550 87	1180 5550 87
wet, integrated multi-disc brake wet brakes on cardan shaft			pneumatic, wet, integrated multi-disc brake Profi version: wet, integrated multi-disc brake; Profi versions: air brakes, spring-loaded handbrake Profi version: FBS2: Fendt dual-circuit four-wheel braking system; Power version: single-circuit braking system				pneumatic, wet, integrated multi-disc brake Profi version: wet, integrated multi-disc brake; Power version: AWD engagement Profi and Power versions: air brakes, spring-loaded handbrake Profi version: FBS2: Fendt dual-circuit four-wheel braking system; Power version: single-circuit braking system					
7900 12500 4600 2000 5240 2550 3050 552 2770 1940 1920 5,5	7900 12500 4600 2000 5240 2550 3050 552 2770 1940 1920 5,5	7900 12500 4600 2000 5240 2550 3050 552 2770 1940 1920 5,5	9300 14000 - 16000 <sup>13)</sup> 4920-8920 <sup>13)</sup>	9300 14000 - 16000 <sup>13)</sup> 4920-8920 <sup>13)</sup>	9450 14000 - 16000 <sup>13)</sup> 4740-7740 <sup>13)</sup>	9450 14000 - 16000 <sup>13)</sup> 4740-7740 <sup>13)</sup>	10700 15000 - 18000 <sup>13)</sup> 4300-7300 <sup>13)</sup>	10760 15000 - 18000 <sup>13)</sup> 4240-7240 <sup>13)</sup>	10760 15000 - 18000 <sup>13)</sup> 4240-7240 <sup>13)</sup>	10760 15000 - 18000 <sup>13)</sup> 4240-7240 <sup>13)</sup>	10830 15000 - 18000 <sup>13)</sup> 4170-7170 <sup>13)</sup>	10830 15000 - 18000 <sup>13)</sup> 4170-7170 <sup>13)</sup>
4,0 12 / 180 Ah 14V / 200 A			4,0 12 V / 170 Ah 14V / 2 x 150 A				4,7 12 V / 170 Ah 14V / 2 x 150 A					
VisioPlus-cabin, side and rear windows, roof hatch, ventilation system with inf. adj. blower in roof, hot water heating with three-speed blower, air-conditioning			5-pillar large-sized cab, 3-point pneumatic suspension system with pitch and roll compensation, tinted front, side and rear windows, roof hatch, auto climate control				5-pillar large-sized cab, 3-point pneumatic suspension system with pitch and roll compensation, tinted front, side and rear windows, roof hatch, automatic climate control					
540/65 R30 650/65 R42	540/65 R30 650/65 R42	540/65 R30 650/65 R42	540/65R30 650/65R42	540/65R30 650/65R42	540/65R34 650/85R38	540/65R34 650/85R38	540/65R34 <sup>14)</sup> 540/65R34 <sup>15)</sup>	540/65R34 <sup>14)</sup> 600/65R34 <sup>15)</sup>	600/65R34 <sup>14)</sup> 600/65R34 <sup>15)</sup>	600/65R34 <sup>14)</sup> 600/65R34 <sup>15)</sup>	600/65R34 <sup>14)</sup> 600/70R34 <sup>15)</sup>	600/65R34 <sup>14)</sup> 600/70R34 <sup>15)</sup>
540/65 R30 650/65 R42			540/65R30 650/65R42				540/65R34 <sup>14)</sup> 600/65R34 <sup>15)</sup>					
540/65 R30 650/65 R42			540/65R30 650/65R42				540/65R34 <sup>14)</sup> 600/65R34 <sup>15)</sup>					

<sup>1)</sup> = optional <sup>2)</sup> = Power specifications for registration, <sup>3)</sup> = with standard tyres, <sup>4)</sup> = can also be used as single-acting, <sup>5)</sup> = depending on country regulations, <sup>6)</sup> = SHPD oil, <sup>7)</sup> = is halved when using RME, <sup>8)</sup> = without steering brake <sup>9)</sup> = rear-wheel drive version, <sup>10)</sup> = for perm. overall weight of 7500 kg, <sup>11)</sup> = only Profi version with dual-circuit braking system, <sup>12)</sup> = optional single-circuit braking system, only 50 km/h, <sup>13)</sup> = depends on the braking system and perm. top speed, <sup>14)</sup> = Power version (50 km/h) <sup>15)</sup> = Profi version (60 km/h)

We are ready for all operations – you too?

# Leaders drive Fendt



Sales agent:

All data regarding delivery, appearance, performance, dimensions and weight, fuel consumption and running costs of the vehicles correspond with the latest information available at the time of going to press. Changes may be made before the time of purchase. Your Fendt dealer will be pleased to supply you with up-to-date information.



AGCO GmbH – Fendt Marketing  
D-87616 Marktobendorf  
Fax +49 (0) 8342 / 77-220 • [www.fendt.com](http://www.fendt.com)