

Specifications

MODEL			Type of beam	Working width cm	Under-beam clearance	No. of furrows	Weight (Kg)					Lift requirement (Kg)					
TYPE	Interbody clearance cm	Head-stock					2-F	3-F	4-F	5-F	6-F	2-F	3-F	4-F	5-F	6-F	
EM	85/100	110	Autom.	35/40/45	70/75	2 - 3	780	990	-	-	-	1200	2200	-	-	-	
EM	85/100	200	"	35/40/45	70/75	3 - 5	-	1040	1290	1430	-	-	2450	3400	4900	-	
LM	85/100	110	Shearbolt	35/40/45	70/80	2 - 3	670	890	-	-	-	1100	1300	-	-	-	
LM	85/100	200	"	35/40/45	70/80	3 - 5	-	920	1110	1330	-	-	1500	2400	3700	-	
ES	80/95	110	Autom.	30 - 50	70/75	2 - 3	770	870	-	-	-	1200	2200	-	-	-	
ES	80/95	200	"	30 - 50	70/75	3 - 5	-	900	1000	1300	-	-	2300	3600	4700	-	
LS	80/95	110	Shearbolt	30 - 50	70/80	2 - 3	730	850	-	-	-	1000	1700	-	-	-	
LS	80/95	200	"	30 - 50	70/80	3 - 5	-	900	1010	1390	-	-	1900	2700	3600	-	
LS	110	200	"	35 - 55	70/80	3 - 4	-	960	1060	-	-	-	2700	2900	-	-	
ED	85/100	200	Autom.	30 - 50	70/75	3 - 5	-	990	1340	1540	-	-	2600	3900	5400	-	
ED	115	200	"	40 - 55	70/75	3 - 5	-	1050	1490	1720	-	-	2800	4600	5600	-	
ED	85/100	300	"	30 - 50	70/75	3 - 5	-	1500	1700	1900	-	-	2900	4200	6400	-	
ED	115	300	"	40 - 55	70/75	4 - 5	-	-	1900	2100	-	-	4800	7600	-	-	
LD	85/100	110	Shearbolt	30 - 50	70/80	2 - 3	660	860	-	-	-	1400	2100	-	-	-	
LD	85/100	200	"	30 - 50	70/80	3 - 5	-	920	1150	1360	-	-	2600	3100	4600	-	
LD	115	200	"	40 - 55	70/80	2 - 4	810	1000	1190	-	-	1800	2700	3600	-	-	
LD-HD	85/100	300	"	30 - 45	70/80	4 - 6	-	-	1250	1510	1950	-	-	3200	4400	6800	
LD-HD	115	300	"	40 - 55	70/80	4 - 5	-	-	1460	1780	-	-	-	3900	5200	-	
EG	85/100	200	Autom.	30 - 55	70/75	3 - 4	-	1100	1370	-	-	-	2900	4300	-	-	
EG-HD	85/100	300	"	30 - 55	70/75	4 - 6	-	-	1550	1800	2300	-	-	4500	5800	8200	
LB	85/100	200	Shearbolt	30 - 55	70/80	3 - 5	-	1020	1210	1400	-	-	2500	3700	4800	-	
LB	115	200	"	30 - 55	70/80	3 - 4	-	1080	1310	-	-	-	2900	3800	-	-	
LB-HB	85/100	300	"	30 - 50	70/80	4 - 6	-	-	1350	1600	2000	-	-	3500	5100	6400	
VX	85/100	200	Shearbolt	30 - 50	70/75	3 - 5	-	870	1080	1200	-	-	1900	2800	3500	-	
EO HD	85/100	300	Autom.	30 - 50	70/75	4 - 7	-	-	2000	2200	2400	2680	-	5500	6200	7700	10300
LO HD	85/100	300	Shearbolt	30 - 50	70/80	4 - 7	-	1800	2000	2200	2400	-	4700	5200	6200	8600	

Most models can be extended by one body. All weights are given without optional equipment (net weights). The lift-requirements are given with the following equipment: depth wheel, one coulter and skimmers for all furrows.

Weights and lifting requirements are given for ploughs with 85cm 'interbody clearance'. For ploughs with 100cm clearance, please adjust according to the following: Weight + 15 Kgs/body, lifting requirement + 35 Kgs/body.

Most ploughs with stepless ploughing width and interbody clearance of 80/85 cm have a working width between 30-45 cm, while ploughs with 95/100 cm have a working width between 35-50 cm.