

TECHNICAL SPECIFICATION

Applications	Tractor
Description	AGRIMAX ELOS has been designed to enhance top traction performance even under particularly awkward operating conditions on wet terrains such as paddy fields or marshland. The tread design has been especially developed to ensure optimum self-cleaning properties, which are essential for operations on muddy land and during transfers. To optimize the farmers' productivity reducing machine downtime, sidewall protectors have been integrated into the design of the AGRIMAX ELOS tire to ensure maximum protection against possible damages at any time.

Pattern Name **AGRIMAX ELOS**

Version	STANDARD
Type	TL
Tire Size	480/80 R 38
LI/SS	149 A8/B

Dimensions (U/M International standard)

Section Width (mm)	489
Overall Diameter (mm)	1803
Static Loaded Radius (mm)	821
Rolling Circumference (mm)	5356
SRI	875
Rim Rec	W 16 L
Rim Alt	W 15 L ; DW 16 L



LOAD CAPACITY TABLE (kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1790	2080	2375	2665	2960	3250
40	1790	2080	2375	2665	2960	3250
30	1915	2230	2545	2855	3170	3480
10 LT	2400	2790	3180	3575	3965	4355
10 HT	1915	2230	2545	2855	3170	3480