

TECHNICAL SPECIFICATION

Applications	Tractor
Description	AGRIMAX ELOS has been designed to enhance top traction performance even under particularly awkward operating conditions on wet terrains such as paddy fields or marshland. The tread design has been especially developed to ensure optimum self-cleaning properties, which are essential for operations on muddy land and during transfers. To optimize the farmers' productivity reducing machine downtime, sidewall protectors have been integrated into the design of the AGRIMAX ELOS tire to ensure maximum protection against possible damages at any time.

Pattern Name **AGRIMAX ELOS**

Version	STANDARD
Type	TL
Tire Size	480/80 R 42
LI/SS	151 A8/B

Dimensions (U/M International standard)

Section Width (mm)	489
Overall Diameter (mm)	1890
Static Loaded Radius (mm)	857
Rolling Circumference (mm)	5600
SRI	875
Rim Rec	DW 16 L
Rim Alt	DD 16 L ; W 16 L



LOAD CAPACITY TABLE (kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1900	2210	2520	2830	3140	3450
40	1900	2210	2520	2830	3140	3450
30	2035	2365	2700	3030	3365	3695
10 LT	2545	2960	3380	3795	4210	4625
10 HT	2035	2365	2700	3030	3365	3695