

TECHNICAL SPECIFICATION

Applications Tractor

Description AGRIMAX ELOS has been designed to enhance top traction performance even under particularly awkward operating conditions on wet terrains such as paddy fields or marshland. The tread design has been especially developed to ensure optimum self-cleaning properties, which are essential for operations on muddy land and during transfers. To optimize the farmers' productivity reducing machine downtime, sidewall protectors have been integrated into the design of the AGRIMAX ELOS tire to ensure maximum protection against possible damages at any time.

Pattern Name **AGRIMAX ELOS**

Version STANDARD
Type TL
Tire Size 710/70 R 38
LI/SS 178 A8/B
TKPH 1



Dimensions (U/M International standard)

Section Width (mm) 716
Overall Diameter (mm) 2019
Static Loaded Radius (mm) 915
Rolling Circumference (mm) 6103
SRI 975
Rim Rec DW 23 B
Rim Alt DW 25 B

LOAD CAPACITY TABLE (kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6
50	2775	3225	3675	4200	4650	5100	5625	5925	6525	7050	7500
40	2775	3225	3675	4200	4650	5100	5625	5925	6525	7050	7500
30	2970	3455	3935	4495	4980	5460	6020	6340	6985	7545	8025
10 LT	3720	4325	4925	5630	6235	6835	7540	7940	8745	9450	10050
10 HT	2970	3455	3935	4495	4980	5460	6020	6340	6985	7545	8025