

TECHNICAL SPECIFICATION

Applications	Vineyard Harvester / Tractor
Description	AGRIMAX RT 657 is the ideal tire for soil tillage and on-the-road usage; some sizes are also suitable for vineyard harvesting. This tire guarantees an excellent driving comfort as well as significant fuel savings. Agrimax RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

Pattern Name **AGRIMAX RT 657**

Version	STANDARD
Type	TL
Tire Size	420/65 R 28
LI/SS	135 D/138 A8

Dimensions (U/M International standard)

Section Width (mm)	418
Overall Diameter (mm)	1257
Static Loaded Radius (mm)	584
Rolling Circumference (mm)	3824
SRI	600
Rim Rec	W 13
Rim Alt	W 12 ; W 11



LOAD CAPACITY TABLE (kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1025	1180	1355	1530	1705	1875	2030	2180
50	1080	1240	1420	1605	1790	1970	2130	2290
40	1110	1275	1465	1655	1845	2030	2195	2360
25	1215	1400	1605	1810	2020	2225	2405	2585
10	1540	1770	2030	2290	2555	2815	3045	3270