

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor / Sprayer

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction on all surfaces at any time. Description

Pattern Name AGRIMAX RT 765

STANDARD Version

Туре

Tire Size 320/70 R 20 LI/SS 123 A8/B

Dimensions (U/M International strandard)

Section Width (mm) 319 Overall Diameter (mm) 982 Static Loaded Radius (mm) 445 Rolling Circumference (mm) 2965 SRI 475 Rim Rec W 10 W 9 ; W 11 Rim Alt



LOAD CAPACITY TABLE (kg)

| km/h / bar | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|-----|------|------|------|------|------|------|------|
| 50 | 730 | 840 | 965 | 1085 | 1210 | 1335 | 1445 | 1550 |
| 40 | 730 | 840 | 965 | 1085 | 1210 | 1335 | 1445 | 1550 |
| 30 | 785 | 900 | 1030 | 1165 | 1295 | 1430 | 1545 | 1660 |
| 10 LT | 980 | 1125 | 1290 | 1460 | 1625 | 1790 | 1935 | 2080 |
| 10 HT | 785 | 900 | 1030 | 1165 | 1295 | 1430 | 1545 | 1660 |