

## TECHNICAL SPECIFICATION

Applications	Vineyard Harvester / Tractor / Sprayer
Description	AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction on all surfaces at any time.

### Pattern Name **AGRIMAX RT 765**

Version	STANDARD
Type	TL
Tire Size	620/70 R 38
LI/SS	170 A8/B

#### Dimensions (U/M International standard)

Section Width (mm)	625
Overall Diameter (mm)	1833
Static Loaded Radius (mm)	828
Rolling Circumference (mm)	5591
SRI	875
Rim Rec	DW 20 B



#### LOAD CAPACITY TABLE (kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
50	2340	2760	3180	3540	3960	4320	4680	5100	5580	6000
40	2340	2760	3180	3540	3960	4320	4680	5100	5580	6000
30	2505	2955	3405	3790	4240	4625	5010	5460	5975	6420
10LT	3140	3700	4265	4745	5310	5790	6275	6835	7480	8040
10HT	2505	2955	3405	3790	4240	4625	5010	5460	5975	6420