

## TECHNICAL SPECIFICATION

Applications: Vineyard Harvester / Tractor / Sprayer  
 Description: AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

**Pattern Name      AGRIMAX RT 855**

Version: STANDARD  
 Type: TL  
 Tire Size: 320/85 R 20  
 LI/SS: 119 A8/B



Dimensions (U/M International standard)  
 Section Width (mm): 329  
 Overall Diameter (mm): 1052  
 Static Loaded Radius (mm): 467  
 Rolling Circumference (mm): 3100  
 SRI: 500  
 Rim Rec: W 11  
 Rim Alt: W 9 ; W 10

**LOAD CAPACITY TABLE (kg)**

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	750	875	995	1120	1240	1360
40	750	875	995	1120	1240	1360
30	805	935	1070	1200	1330	1460
10 LT	1005	1170	1335	1500	1665	1825
10 HT	805	935	1070	1200	1330	1460