

TECHNICAL SPECIFICATION

| | |
|--------------|--|
| Applications | Vineyard Harvester / Tractor / Sprayer |
| Description | AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage. |

Pattern Name **AGRIMAX RT 855**

| | |
|-----------|-------------|
| Version | STANDARD |
| Type | TL |
| Tire Size | 320/85 R 24 |
| LI/SS | 122 A8/B |

Dimensions (U/M International standard)

| | |
|----------------------------|------------|
| Section Width (mm) | 329 |
| Overall Diameter (mm) | 1154 |
| Static Loaded Radius (mm) | 519 |
| Rolling Circumference (mm) | 3413 |
| SRI | 550 |
| Rim Rec | W 11 |
| Rim Alt | W 9 ; W 10 |



LOAD CAPACITY TABLE (kg)

| km/h / bar | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 50 | 825 | 960 | 1095 | 1230 | 1365 | 1500 |
| 40 | 825 | 960 | 1095 | 1230 | 1365 | 1500 |
| 30 | 885 | 1030 | 1175 | 1320 | 1465 | 1605 |
| 10 LT | 1110 | 1290 | 1470 | 1650 | 1830 | 2010 |
| 10 HT | 885 | 1030 | 1175 | 1320 | 1465 | 1605 |