

TECHNICAL SPECIFICATION

Applications Vineyard Harvester / Tractor / Sprayer

Description AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for row crops, spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

Pattern Name **AGRIMAX RT 855**

Version STANDARD

Type TL

Tire Size 420/80 R 46

LI/SS 151 D/162 A2



Dimensions (U/M International standard)

Section Width (mm) 418

Overall Diameter (mm) 1840

Static Loaded Radius (mm) 863

Rolling Circumference (mm) 5619

SRI 875

Rim Rec W 13

Rim Alt W 12

LOAD CAPACITY TABLE (kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1625	1865	2140	2415	2695	2970	3210	3450
50	1705	1960	2250	2540	2830	3120	3375	3625
40	1780	2045	2345	2650	2950	3255	3520	3780
30	1870	2145	2465	2780	3100	3415	3695	3970
10	2235	2565	2945	3325	3705	4085	4420	4750
10 LT	2175	2500	2870	3240	3610	3980	4305	4625
10 HT	1870	2145	2465	2780	3100	3415	3695	3970