

## TECHNICAL SPECIFICATION

Applications	Vineyard Harvester / Tractor / Sprayer
Description	AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying. The special tread design with a rounded shoulder provides excellent traction performance and continuous contact on the land in order to protect both valuable crops and soil from damage.

### Pattern Name **AGRIMAX RT 955**

Version	STANDARD
Type	TL
Tire Size	270/95 R 54
LI/SS	146 A8/B

#### Dimensions (U/M International standard)

Section Width (mm)	275
Overall Diameter (mm)	1885
Static Loaded Radius (mm)	878
Rolling Circumference (mm)	5815
SRI	925
Rim Rec	W 9
Rim Alt	W 8 ; W 10



#### LOAD CAPACITY TABLE (kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	1170	1530	1860	2040	2160	2370	2580	2790	3000	-
40	1170	1530	1860	2040	2160	2370	2580	2790	3000	-
30	1255	1640	1995	2185	2315	2540	2765	2990	3210	-
10	1395	1755	2160	2565	2970	3060	3420	3780	4140	4500