

## TECHNICAL SPECIFICATION

**Applications** Vineyard Harvester / Tractor / Sprayer

**Description** AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying. The special tread design with a rounded shoulder provides excellent traction performance and continuous contact on the land in order to protect both valuable crops and soil from damage.

**Pattern Name**      **AGRIMAX RT 955**

**Version**                STANDARD  
**Type**                    TL  
**Tire Size**              340/85 R 48  
**LI/SS**                  152 A8/B



**Dimensions (U/M International standard)**

**Section Width (mm)**      353  
**Overall Diameter (mm)**    1797  
**Static Loaded Radius (mm)** 855  
**Rolling Circumference (mm)** 5572  
**SRI**                        875  
**Rim Rec**                 W 12  
**Rim Alt**                 W 11

**LOAD CAPACITY TABLE (kg)**

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	1385	1815	2205	2415	2560	2805	3055	3305	3550	-
40	1385	1815	2205	2415	2560	2805	3055	3305	3550	-
30	1485	1940	2360	2585	2740	3005	3270	3535	3800	-
10	1655	2080	2560	3040	3515	3625	4050	4475	4900	5325