

TECHNICAL SPECIFICATION

Applications	High Power Tractor
Description	As a result of the recent evolution that high-powered tractors have seen in terms of both technology and performance, also tires are expected to meet this challenging demand. AGRIMAX V-FLECTO is BKT's response. This tire excels in both performance and reliability offering extraordinary resistance against highest stress levels as well as excellent speed levels even on paved roads. The advantages? More productivity and a significant reduction of operating costs - whatever the task.

Pattern Name **AGRIMAX V - FLECTO**

Version	STANDARD
Type	TL
Tire Size	VF 600/60 R 38 NRO
LI/SS	166 D
TKPH	1

Dimensions (U/M International standard)

Section Width (mm)	587
Overall Diameter (mm)	1685
Static Loaded Radius (mm)	757
Rolling Circumference (mm)	5044
SRI	800
Rim Rec	DW 20 B
Rim Alt	DW 18 L



LOAD CAPACITY TABLE (kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	2365	2750	3185	3570	3955	4340	4820
From 10 TO 65 km/h	2600	3025	3500	3925	4350	4770	5300
DUAL FITMENT	2290	2665	3080	3455	3830	4200	4665