

TECHNICAL SPECIFICATION

Applications Trailer / Telehandler / Small Tractor / Implement Machinery / Hay Harvester / Baler
 Description AS 504 is an agro-industrial tire mainly designed for transport and soil tillage operations. In some sizes, AS 504 is suitable for loading and hay harvesting applications. This tire, which features excellent self-cleaning properties and increased grip, is ideal for muddy grounds. There are several versions of the AS 504 tire to meet specific end-user requirements.

Pattern Name AS 504
 Version STANDARD
 Type TT
 Tire Size 7.00 - 12
 PR 4



Dimensions (U/M International standard)
 Section Width (mm) 187
 Overall Diameter (mm) 683
 Static Loaded Radius (mm) 300
 Rolling Circumference (mm) 2001
 Rim Rec 4.5

LOAD CAPACITY TABLE (kg)

| km/h / bar | 1.70 |
|------------|------|
| 10 FR | 785 |
| 25 FR | 665 |
| 30 FR | 625 |
| 40 FR | 560 |
| 10 DW | 540 |
| 25 DW | 460 |
| 30 DW | 430 |
| 40 DW | 385 |

* Tolerances: Overall Diameter \pm 2% | Section Width \pm 2% | Rolling Circumference \pm 2.5%