



# ENDRESS

## Power Generators

### ESE 908 DBG ES DIN Super Silent Plus

Order No. **156413**



#### Main features

Alternator type	<b>Duplex</b>
Continuous Power 3~ [kVA/kW]	9.0/7.2
Continuous Power 1~ [kVA/kW]	6.0/5.4
Nominal voltage [V]	400/230
Nominal Current [A]	12.9/26.1
Power factor cos (phi)	0,8
Frequency [Hz]	50
Protection Class [IP]	54

#### Engine

Engine Type	B&S Vanguard 16 HP
Design	2-cylinder. 4-stroke OHV
Displacement [ccm]	479
Output 3000 rpm	9,5
CO2 emissions [g / kWh]	927,21
CO2 test procedure	G1
Fuel	Petrol
Fuel tank capacity [l]	12
Fuel consumption @ 75% PRP [L/h]	2,4
Running time @ 75% PRP	5
Starting system	Electric starter
Sound power level LWA [db(A)]	89
Weight in kg ca.	132
Dimensions L x W x H [mm]	820 x 440 x 580
Shockproof sockets	3 x 230V 16A 2 x 400V CEE 16A

This CO2 measurement results from testing over a fixed test cycle under laboratory conditions a(n) (parent) engine representative of the engine type (engine family) and shall not imply or express any guarantee of the performance of a particular engine'.

Power ratings according to ISO 8528-1: 2005

Technical data and illustrations are not binding. We assume no liability for misprints.

2020-2-19

**ENDRESS Elektrogerätebau GmbH**  
Neckartenzlinger Str. 39  
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0  
Fax.: +49 (0) 7123-9737-50  
www.endress-generators.de



**Advantages at a glance**

- Comprehensive functions, safe and simple operation
- ➔ DUPLEX current quality without compromise
- Special equipment and accessories, available for many requirements
- Fitted according to DIN 14685-1
- Multifunctional control display E-MCS 4.0 - a clear system
- A large tank for long operation – with re-fuelling
- Emergency start function over the recoil starter

**Equipment features**

- Insulation monitoring – without shut-off
- 3-way fuel cock for external refuelling
- Multifunction control display E-MCS 4.0
- Fuel level indicator over the E-MCS 4.0
- Lack of oil automatic switch-off
- Alternator overload protection
- Starter battery 12 V/20 A
- Folding handles
- Vehicle tool kit

**Special equipment - not retrofittable**

	Order No.
External start Nato socket	163 000
Charging current socket DIN 14690	163 010
Charging current socket MagCode	163 018
➔ ECOtronic system	163 020
Automatic Choke	163 030
Insulation monitoring device with shut-off	163 071
Beos charging current socket	163 080
FireCAN	163 140
Remote start device	163 150
Colour red RAL 3000	163 180

**Accessories**

	Order No.
Exhaust hose (1.5 m)	<b>163 120</b>
Exhaust hose (2.5 m)	<b>163 121</b>
90° Adapter for Exhaust hose	<b>163 130</b>
Hose for refuelling without a canister	<b>E100 592</b>
Transport carriage for a 8 series DIN frame	<b>163 100</b>
Wheel Kit for the 5 and 8 series DIN frame	<b>163 102</b>

выразить любую гарантию работы конкретного двигателя.

Power ratings according to ISO 8528-1: 2005

Technical data and illustrations are not binding. We assume no liability for misprints.

2020-2-19