

GL 5 Picking Series horizontal electronic order picker

Technical data in line with VDI 2198

as at: 04/2012

Identification	1.1	Manufacturer (abbreviation)	Icem	
	1.2	Manufacturer's type designation	GL 5 Picking	
	1.3	Drive	electric	
	1.4	Type of operation	stand	
	1.5	Load capacity/rated load	Q (t)	0.5
	1.6	Load centre distance	c (mm)	600
	1.8	Load distance, centre of drive axle to fork	x (mm)	701
	1.9	Wheelbase	y (mm)	1784
	Weights	2.1	Service weight incl. battery (see line 6.5)	kg
2.2		Axle loading, laden front/rear	kg	878/772
2.3		Axle loading, unladen front/rear	kg	850/300
Wheels, Chassis	3.1	Tyres	PU	
	3.2	Tyre size, front	mm	Ø 250
	3.3	Tyre size, rear	mm	Ø 85
	3.4	Additional wheels (dimensions)	mm	Ø 150
	3.5	Wheels, number front/rear (x = driven wheels)		1x+2/2
	3.6	Track width, front	b ₁₀ (mm)	740
	3.7	Track width, rear	b ₁₁ (mm)	390
Basic dimensions	4.4	Lift height	h ₃ (mm)	1095
	4.8	Standing height	h ₇ (mm)	105
	4.9	Height of tiller in drive position min./max.	h ₁₄ (mm)	1285/1630
	4.14	Standing height, elevated	h ₁₂ (mm)	1200
	4.15	Lowered height	h ₁₃ (mm)	90
	4.19	Overall length	l ₁ (mm)	2470
	4.20	Length to face of forks	l ₂ (mm)	1320
	4.21	Overall width	b ₁ (mm)	860
	4.22	Fork dimensions	s/e/l (mm)	70/180/1150
	4.25	Width over forks	b ₅ (mm)	570
	4.32	Ground clearance, centre of wheelbase	M ₂ (mm)	30
4.34	Aisle width for pallets 800x1200 (b ₁₂ xl ₆)	Ast (mm)	2741 ⁽¹⁾	
4.35	Turning radius	Wa (mm)	2042	
Perform. data	5.1	Travel speed, laden/unladen	km/h	7.5/9.0
	5.2	Lift speed, laden/unladen	m/s	0.10/0.14
	5.3	Lowering speed, laden/unladen	m/s	0.30/0.25
	5.8	Max. gradient performance, laden/unladen	%	5/10
	5.10	Service brake		electronic
Electric eng.	6.1	Drive motor rating S ₂ 60min	kW	2
	6.2	Lift motor rating at S ₃ 10%	kW	2.2
	6.4	Battery voltage, nominal capacity K ₅	V/Ah	24/320
	6.5	Battery weight	kg	280
	8.1	Type of drive control		AC
8.4	Sound level at driver's ear according to EN 12 053	dB (A)	70	

(1) diagonal to VDI: + 141 mm

GL 5 Picking Series horizontal electronic order picker

Technical data in line with VDI 2198

as at: 04/2012

