

FORKLIFT TRUCK (BATTERY/LPG)



Specifications (BATTERY)

MODEL	HBF 15 III	HBF 18 III	HBF 20-7	HBF 25-7	HBF 30-7	HBF 32-7	HBR 14-7	HBR 15-7	HBR 18-7	HBR 20-7
Load capacity (kg,lb)	1,500(3,000)	1,750(3,500)	2,000(4,000)	2,500(5,000)	3,000(6,000)	3,200(6,500)	1,350(2,975)	1,500(3,300)	1,800(3,950)	2,000(4,400)
Load center (mm,in)	500(19.7)	500(19.7)	500(24)	500(24)	500(24)	500(24)	500(19.6)	500(19.6)	500(19.6)	500(19.6)
Travel speed (km/h,mpg)	14.7(9.2)	14.5(9.0)	15.8(9.8)	15.3(9.5)	15.2(9.4)	14.9(9.2)	10.9(6.8)	10.7(6.6)	10.2(6.3)	11.8(7.3)
Max. Lifting height (mm,in)	3,300(130)	3,300(130)	3,300(129.9)	3,300(129.9)	3,300(129.9)	3,200(125.9)	3,000(118.1)	3,000(118.1)	3,000(118.1)	3,000(118.1)
Free Lifting height (mm,in)	150(5.9)	150(5.9)	155(6.1)	155(6.1)	155(6.1)	155(6.1)	357(14)	357(14)	357(14)	415(16.3)
Outside turning radius min. (mm,in)	1,790(69.9)	1,830(71.1)	1,960(77.1)	2,000(78.7)	2,235(87.9)	2,250(88.5)	1,550(61)	1,640(64.6)	1,775(69.9)	1,795(70.6)
Overall length to fork face (mm,in)	2,859(113)	2,899(114)	2,267(89.2)	2,322(91.4)	2,507(98.7)	2,527(99.0)	2,085(82)	2,085(82)	2,085(82)	2,330(91.7)
Overall guard height (mm,in)	2,145(83)	2,145(83)	2,200(87.4)	2,200(87.4)	2,250(88.6)	2,250(88.6)	2,258(88.8)	2,258(88.8)	2,258(88.8)	2,294(90.3)
Drive motor (sem) (W,ps)	7.5(10.2)	7.5(10.2)	10(7.4)	10.3(13.8)	10.3(13.8)	10.3(13.8)	5.0(6.8)	5.0(6.8)	5.0(6.8)	5.0(6.8)
Pump motor (series) (kw,ps)	8.5(11.6)	8.5(11.6)	12.2(16.6)	15.5(20.8)	15.5(20.8)	15.5(20.8)	9.5(12.9)	9.5(12.9)	9.5(12.9)	9.5(12.9)

Specifications (LPG)

MODEL	HLF15-5	HLF18-5	20L-7	25L-7	30L-7
Engine model	MITSUBISHI 4G64-33HL	MITSUBISHI 4G64-33HL	HMC BETA	HMC BETA	HMC BETA
Rated power (ps,rpm) / (kw,rpm)	39/2,300(29/2,300)	39/2,300(28.7/2,300)	37/2,450	37/2,450	37/2,450
Load capacity (kg,lb)	1,500(3,000)	1,750(3,500)	2,000(4,000)	2,500(5,000)	3,000(6,000)
Load center (mm,in)	500(24)	500(24)	500(24)	500(24)	500(24)
Travel speed (km/h,mpg)	20.6(12.8)	20.6(12.8)	20.6(12.8)	20.6(12.8)	21.6(13.4)
Max. Lifting height (mm,in)	3,300(130)	3,300(130)	3,300(130)	3,300(130)	3,300(130)
Free Lifting height (mm,in)	145(5.7)	145(5.7)	155(6.1)	155(6.1)	155(6.1)
Outside turning radius min. (mm,in)	1,940(76.3)	1,970(77.6)	2,252(89.0)	2,300(91.0)	2,393(94.0)
Overall length to fork face (mm,in)	2,170(85.4)	2,200(86.6)	2,527(99)	2,582(102)	2,688(106)
Overall guard height (mm,in)	2,110(83.1)	2,100(83)	2,160(85)	2,160(85)	2,180(86)