

Net Power

197 HP (147kW) at 2,200 rpm

Gross Power

200 HP (149kW) at 2,200 rpm

Bucket Capacity

 $2.7 \text{ m}^3 (3.5\text{yd}^3) \sim 2.8 \text{ m}^3 (3.7\text{yd}^3)$

Operating Weight

16,500kg (36,380lb)



IL955A тм

FUEL EFFICIENT SYSTEM ALLOWS GREAT PERFORMANCE


HL A Series has an eco-friendly, high-performance engine which ensures both excellent fuel efficiency and high power.

With outstanding operating performance proven by rigorous tests at various work sites, it will satisfy any customer's needs.



SPECIFICATIONS & DIMENSIONS





Specifications

ITEM			HL955A TM
Type		-	Hydraulic type
Engine	Maker / Model	-	CUMMINS / B6.7
	Gross power	HP(kW)/rpm	200 (149) / 2,200
	Net power	HP(kW)/rpm	197 (147) / 2,200
	Maximum torque	$Kgf \cdot m(lb \cdot ft)/rpm$	101 (730) / 1,300
	No. of cylinders	ea	6
Operating weight		kg (lb)	16,500 (36,380)
Bucket capacity	Heaped	m³(yd³)	2.7 (3.5)
	Struck	m³(yd³)	2.3 (3.0)
Breakout force-bucket		kg (lb)	12,820 (28,260)
Tipping load	Straight	kg (lb)	11,000 (24,250)
	Full turn	kg (lb)	9,550 (21,050)

^{*} Engine Type: 4-cycle, water cooled, turbocharged, diesel, direct injection

Dimensions

UNIT		HL955A TM	
Α	mm (ft-in)	2,850 (9' 4")	
В	mm (ft-in)	1,360 (4' 6")	
C	mm (ft-in)	2,010 (6' 7")	
D	mm (ft-in)	7,820 (25' 8")	
Е	mm (ft-in)	5,420 (17' 9")	
F	mm (ft-in)	4,020 (13' 2")	
Н	mm (ft-in)	3,050 (10')	
-	mm (ft-in)	410 (1' 4")	
Κ	mm (ft-in)	3,390 (11' 1")	
L	mm (ft-in)	2,530 (8' 4")	
М	deg	50	
Ν	dea	50	

A HYUNDAI CONSTRUCTION EQUIPMENT

Head Office(Sales Office)
3F, Bundang First Tower, 55 Bundang-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, 13591, Korea

6100 Atlantic Boulevard Norcross Ga 30071 U.S.A TEL (1) 847-678-823-7802 FAX (1) 847-678-823-7778

Europe Operation : Hyundai Construction Equipment Europe N.V. Hyundailaan 4,

PLEASE CONTACT