

Multi Purpose Truck (MPT) Tyres

Tyre Size	Pattern	Rim		Unloaded Inflated Dimensions		Static Loaded Radius (mm)	Rolling Circumference ± 2.5 % (mm)	Ply Rating	Type	Load Capacity			
				± 2 %						90 km/h		40 km/h	
		Rec.	Alt.	Section Width (mm)	Overall Diameter (mm)					Max. Load (kgs)	Inflation Pressure (bar)	Max. Load	Inflation Pressure (bar)
10.0/75 - 15.3	MP-567	9	---	258	774	355	2310	10	TT	---	---	1500	3.9
								12	TL	--	--	1700	4.7
								14	TL	--	--	1900	5.5
								18	TL	--	--	2200	7.1
11.5/80 - 15.3	MP-567	9.0		292	868	393	2578	10	TL	--	--	1900	3.4
								14	TT	--	--	2430	4.75
								18	TL	--	--	2800	6.0
10.5 - 18	MP-567	9	9 SDC	270	905	415	2700	10	TT	1700	3.75	1955	3.75
								12	TL	1900	4.5	2190	4.5
12.5 - 18	MP-567	11.0	12 SDC	325	990	450	2940	10	TT	1800	3.0	2070	3.0
								12	TT	1950	3.5	2245	3.5
								16	TL	2250	4.5	2585	0.5
18 - 19.5	MP-567	14.00	---	460	1104	498	3280	16	TL	4500 *	6	4700	6
								18	TL	5150 *	7.25	5460	7.25
10.5 - 20	MP-567	9	9 SDC	270	955	445	2880	10	TT	1800	3.75	2070	3.75
12.5 - 20	MP-567	11.0	12 SDC	325	1040	475	3090	10	TT	1850	3	2130	3
								12	TT	2000	3.5	2300	3.5
14.5 - 20	MP-567	11	12 SDC	360	1116	495	3315	10	TL	2000	2.5	2300	2.5
								12	TL	2240	3	2580	3
								14	TL	2430	3.5	2790	3.5
								16	TL	2575	4	2960	4
								18	TL	2725	4.5	3135	4.5
405/70 - 20 (16.0/70 - 20)	MP-567	13 SDC	12	405	1128	490	3350	14	TL	2900	3.5	3340	3.5

All tyres conform to T&RA standards

*These loads are for 50 km/h (Its highest operating speed)