

Cab	SR-Standard	SR-Deluxe	SR-Deluxe
Standard equipment	Heater Pro Deluxe seat Buddy seat	Heater Pro Deluxe seat Buddy seat	Heater/ Air cond. Pro Deluxe seat Buddy seat
Optional	Air pressured seat	Air pressured seat	Air pressured seat
Noise level	80 dB (A)	77 dB (A)	77 dB (A)

Cutting table

Width	4,5 m	5,1 m	5,1 m
Optional width	3,9-5,1 m	3,9-5,1 m	4,2-6,3 m
Cutting height	-0,2...1,3 m	-0,2...1,3 m	-0,2...1,3 m
Knife speed	1020 stroke/min	1020 stroke/min	1020 stroke/min
Straw dividers	Short adjustable	Short adjustable	Short adjustable
Optional	Bow dividers	Bow dividers	Bow dividers

Reel

Diameter	1,05 m	1,05 m	1,05 m
Speed range	0...50 rpm	0...50 rpm	0...50 rpm
Reel adjustments	Hydraulic	Hydraulic	Hydraulic

Threshing cylinder

Width	1,33 m	1,33 m	1,33 m
Diameter	0,50 m	0,50 m	0,50 m
Number of rasp bars	8	8	8
Speed range	600...1300 rpm	600...1300 rpm	600...1300 rpm
Optional	400...1150	400...1150	400...1150
Speed adjustment	Electrical	Electrical	Electrical

Pre-treshing cylinder

Width			1,33 m
Diameter			0,40 m

Concave

Area	0,62 m ²	0,62 m ²	0,62 m ²
Angle of wrap	105°	105°	105°
Number of bars	9	9	9
Stepless adj. range	6...42 m	6...42 m	6...42 m
Adjustment type	Mechanical	Electrical	Electrical

Pre-concave

Area			0,41 m
------	--	--	--------

Straw walkers

Number	6	6	6
Area	5,80 m ²	6,30 m ²	6,30 m ²
CSP-separating drum		Option	Standard

Shaker shoe

Top sieve	2,1 + 0,40 m ²	2,1 + 0,40 m ²	2,3 + 0,40 m ²
Bottom sieve	1,6 m ²	1,6 m ²	1,8 m ²

Grain tank

Capacity	5,2 m ³	6,5 m ³	7,6 m ³
Optional capacity	6,5 m ³	-	8,1 m ³ (open unloading)
Unloading height	3,75 m	4,0 m	4,4 m
Optional height	4,0 m	3,75 m	4,0 m (open unloading)


Engine

SisuPower			
Power	136/185 kW/hv	155/210 kW/hv	184/250 kW/hv
Optional engines	155/210 kW/hv	184/250 kW/hv	202/276 kW/hv
Working speed	2000 rpm	2000 rpm	2000 rpm
Number of cyl.	6	6	6
Fuel tank	350 l	350 l	450 l

Transmission

	Hydrostatic	Hydrostatic	Hydrostatic
--	-------------	-------------	-------------

Tyres

Front	650/65 R38	650/65 R38	650/65 R38
Optional	800/65 R32	800/65 R32	800/65 R32
	900/60 R32	900/60 R32	900/60 R32

Rear	380/75 R24	380/75 R24	480/65 R24
Optional	480/65 R24	480/65 R24	540/65 R24

Wheelbase

Front	2,76/2,87 m (650)	2,76/2,87 m (650)	2,90 m (800)
	2,90 m (800)	2,90 m (800)	3,20 m (1050)
	3,20 m (1050)	3,20 m (1050)	

Rear	2,5/2,6 m (380)	2,5/2,6 m (380)	2,5/2,6 m (380)
	2,7 m (480 and 540)	2,7 m (480 and 540)	2,7 m (480 and 540)
Rear, 4WD	2,7 m (480 and 540)	2,7 m (480 and 540)	2,7 m (480 and 540)
Turning radius	7,7 m	7,7 m	8,0 m

Dimensions

Length			
Without table	7,50 m	8,63 m	9,05 m
With table	9,00 m	9,85 m	10,27 m
Width			
Without table	3,4 / 3,5 m (650)	3,4 / 3,5 m (650)	-
	3,7 m (800)	3,7 m (800)	3,70 m (800)
	4,3 m (1050)	4,3 m (1050)	4,30 m (1050)
With table	Cutting width +0,3 m	Cutting width +0,3 m	Cutting width +0,3 m
Height with cab	3,95 m	3,95 m	3,95 m

Weight

W/std table and chopper	11 230 kg	11 700 kg	12 600 kg
-------------------------	-----------	-----------	-----------

Optional extras:

AHC	Combine monitor	Chaff spreader
DHC	Chaff spreader	Rice equipment
Air conditioning	Stone trap	4WD
Radio/Cassette player	Table trailer	Rice kit*
Grain loss indicator	Straw chopper	*SR3035

Specifications are subject to change and may vary from a country to country. Manufacturer reserves right to do changes on products without any notice and without obligation to apply such changes to machines manufactured before.