

**TECHNICAL SPECIFICATION**

Applications                      Trailer / Tractor  
 Description                      TR 135 is best suitable for soil tillage and spraying applications. Some sizes and versions are also suitable for excavators, trailers and harvesters. Traction, self-cleaning properties and stability are key features which make the TR 135 tire the ideal partner even on the most difficult ground conditions.

**Pattern Name**                **TR 135**  
 Version                            STANDARD  
 Type                                TT  
 Tire Size                         14.9 - 28  
 LI/SS                              125 A6  
 PR                                 6



Dimensions (U/M International standard)  
 Section Width (mm)        378  
 Overall Diameter (mm)    1365  
 Static Loaded Radius (mm) 634  
 Rolling Circumference (mm) 4170  
 SRI                                650  
 Rim Rec                         W 13  
 Rim Alt                         W 11 ; W 12

**LOAD CAPACITY TABLE (kg)**

km/h / bar	<b>1.40</b>
30	1650

\* Tolerances: Overall Diameter ± 2% | Section Width ± 2% | Rolling Circumference ± 2.5%

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints.  
 All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..