

## TECHNICAL SPECIFICATION

Applications	Tractor
Description	TR 171 is a deep tread tire suitable for tractors in soil tillage operations. Thanks to its outstanding self-cleaning properties, it is ideal for wet and moist soil. Also in the harshest operating conditions, TR 171 provides excellent traction and extraordinary durability.

<b>Pattern Name</b>	<b>TR 171</b>
Version	STANDARD
Type	TT
Tire Size	16.9 - 30
LI/SS	137 A6
PR	8

### Dimensions (U/M International standard)

Section Width (mm)	430
Overall Diameter (mm)	1490
Static Loaded Radius (mm)	687
Rolling Circumference (mm)	4535
SRI	700
Rim Rec	W 15 L
Rim Alt	W 14 L



### LOAD CAPACITY TABLE (kg)

km/h / bar	1.70
30	2300

\* Tolerances: Overall Diameter  $\pm 2\%$  | Section Width  $\pm 2\%$  | Rolling Circumference  $\pm 2.5\%$

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints.

All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..