

## **TECHNICAL SPECIFICATION**

Applications Description

## Tractor

TRAC FARM is a heavy-duty tire specifically designed for tractors and soil tillage applications. Its strong casing and the deep tread make the tire suitable for the most difficult operating conditions, ensuring the best return on investment during the entire product life-cycle.

## **Pattern Name**

**TRAC FARM** 

Version Туре Tire Size LI/SS PR

STANDARD ΤT 18.4 - 30 149 A6 12



Dimensions (U/M International strandard) Section Width (mm) 467 Overall Diameter (mm) 1550 Static Loaded Radius (mm) 716 Rolling Circumference (mm) 4557 SRI

725

W 16 L W 15 L

LOAD CAPACITY TABLE (kg)
--------------------------

km/h / bar	2.30
30	3250

Rim Rec

Rim Alt

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd.