

**HOLDER
X SERIES**



		1-person-cab	
ENGINE	Kubota 4-cylinder petrol		Kubota 4-cylinder Turbodiesel
Power	32.6 kW (44 HP)		31 kW (42 HP)
Displacement	1605 cm ³		1498 cm ³
Rated speed	2600 rpm		2800 rpm
Cooling system	Water cooling		
Fuel tank capacity	42 l		
DRIVE	Hydrostatic drive, stepless speed regulation, four equal sized wheels		
Speed	0 – 27 km/h		
Brakes	Hydraulic service brake on the front axle, active on all four wheels via the hydrostatic drive, mechanical parking brake on the front axle with two drum brakes		
HYDRAULICS	First circuit 55 l/min at 2600 rpm, second circuit 30 l/min at 2600 rpm, third circuit 5 l/min at 2600 rpm		
Quantity of hydraulic oil	19 l		
Lifting force	Front 750 kg		
WEIGHTS	Includes driver of 75 kg; depends on tyres and equipment		
Empty weight	1280 kg		
Permissible total weight	2300 kg		
Permissible axle load	Front: 1190 kg / rear: 1190 kg		
Tow bar load on the trailer coupling	75 kg		
Towing capacity	Braked 900 kg		
Maximum payload	1020 kg		
DIMENSIONS	Tyres: 20 x 10.00-10		Tyres: 23 x 10.50-12
Wheelbase	1360 mm		
Total length	2870 – 2905 mm		
Total height	1960 mm		2020 mm
Total outer width	1094 mm (without external mirrors)		
Turning circle	2150 mm		
SUCTION SWEEPER			
Container gross / net	1 m ³ / 0.7 m ³		
Fresh water tank	150 l		
Max. sweeping width	2050 mm		